



TRUCK WHEEL PROGRAM

STEEL TRUCK WHEELS - WHITE POWDER COAT FINISH

- E-coat primer and white powder coat finish
- High Strength Steel Alloy For Superior Durability
- Palletized using spacers and shrink wrapped to secure during shipment
- All Wheels include valve stem
- 5 Year Limited Warranty



WHITE POWDER COAT FINISH HUB PILOTED

Size	Art #	Hand Holes	Pilot Type	Bolt Circle (mm)	Bore Dia. (mm)	Disc Thickness (Inch/mm)	Offset (Inch/mm)	Max Load (lbs)	Max Infl (psi)	Weight (lbs)	Valve
22.5 x 8.25	SR22H45*	2	Hub	285.75	220	0.433/11.00	6.62 / 168	7,400	120	69.00	TR572-40
24.5 x 8.25	SR24H31	2	Hub	285.75	220	0.433/11.00	6.63 / 169	7,400	120	84.20	TR572-40
22.5 x 7.50	SR22H27	5	Hub	285.75	220	0.433/11.00	6.49 / 165	7,400	120	77.66	TR572-H22
22.5 x 8.25	SR22H47*	5	Hub	285.75	220	0.433/11.00	6.61 / 168	7,400	120	67.00	TR572-40
22.5 x 9.00	SR22H75	5	Hub	285.75	220	0.610/15.50	7.00 / 178	10,000	130	113.52	V3-20-6
22.5 x 9.00	SR22H95	5	Hub	285.75	220	0.531/13.50	5.27 / 134	10,000	130	95.97	V3-20-6

WHITE POWDER COAT FINISH STUD PILOTED

Size	Art #	Hand Holes	Pilot Type	Bolt Circle (mm)	Bore Dia. (mm)	Disc Thickness (Inch/mm)	Offset (Inch/mm)	Max Load (lbs)	Max Infl (psi)	Weight (lbs)	Valve
22.5 x 8.25	SR22S44*	2	Stud	285.75	222	0.433/11.00	6.62 / 168	7,400	120	69.00	TR572-40
24.5 x 8.25	SR24S31	2	Stud	285.75	222	0.433/11.00	6.63 / 169	7,400	120	84.20	TR572-40

*New lightweight items replace the following:

SR22H45 replaces SR22H35

SR22H47 replaces SR22H57

SR22S44 replaces SR22S34

- **New lightweight items produced with higher tensile strength steel for durability with no variance in disc thickness.**

*Steel wheels are available in additional sizes, please contact your sales representative for additional information:

17.5x6.75 Single and Dual; 19.5x6.75 Dual



TRUCK WHEEL PROGRAM

ALUMINUM TRUCK WHEELS

- Forged Aluminum for Superior Durability
- Palletized using spacers and shrink wrap to secure during shipment
- All Wheels include valve stem
- 4 Year Limited Warranty



MACHINED FINISH

Size	Art #	Hand Holes	Pilot Type	Bolt Circle (mm)	Bore Dia. (mm)	Inset (Inch/mm)	Offset (Inch/mm)	Max Load (lbs)	Max Infl (psi)	Weight (lbs)	Valve
22.5x8.25	DC225H00Y10050M	10	Hub	285.75	220	5.65 / 143.5	6.63 / 169	7,400	130	52.47	TR544D
24.5x8.25	DC245H00Y10052M	10	Hub	285.75	220	5.67 / 144.0	6.62 / 168	7,800	130	62.39	TR544D

SEMI POLISHED (STANDARD POLISHED)

Size	Art #	Hand Holes	Pilot Type	Bolt Circle (mm)	Bore Dia. (mm)	Inset (Inch/mm)	Offset (Inch/mm)	Max Load (lbs)	Max Infl (psi)	Weight (lbs)	Valve
22.5x8.25	DC225H01Y10050P	10	Hub	285.75	220	5.65 / 143.5	6.63 / 169	7,400	130	52.47	TR544D
24.5x8.25	DC245H01Y10052P	10	Hub	285.75	220	5.67 / 144.0	6.62 / 168	7,800	130	62.39	TR544D

* Aluminum wheels are available in additional sizes, please contact your sales representative for additional information:

17.5x6.75; 19.5x6.75; 19.5x7.5; 22.5x7.5; 22.5x9.00; 22.5x11.75; 22.5x13; and 22.5x14



TRUCK WHEEL PROGRAM

DEMOUNTABLE RIM - WHITE POWDER COAT FINISH

- E-coat primer and white powder coat finish
- Palletized using spacers and shrink wrapped to secure during shipment
- All Wheels include valve stem
- 5 Year Limited Warranty



WHITE POWDER COAT FINISH

Size	Art #	Hand Holes	Pilot Type	Bolt Circle (mm)	Bore Dia. (mm)	Disc Thickness (Inch/mm)	Offset (Inch/mm)	Max Load (lbs)	Max Infl (psi)	Weight (lbs)	Valve
22.5 x 8.25	SR22D02	-	-	-	-	-	4.76/121	7,300	120	68.10	-
24.5 x 8.25	SR24D02	-	-	-	-	-	4.76/121	7,300	120	75.16	-